

Figure 8 (Speaker) Cable



Wire & Cable Specification

Construction	
Conductor	Stranded bare copper
Insulation	PVC

Item Codes

Standard

Material No.	Old Code	Cores x Area mm ²	Description	Stranding No./mm	Nom Dim mm	Max DC Resist. @ 20°C Ohms/km	Pack Size *	Approx Mass kg/m
Conductor Size 0.50 mm²								
JSF.5WTBK1	6121	2 x 0.5	BK/WH	14/0.20	1.8 x 4.3	44.5	100m	0.02
JSF.5GYBK*	1878	2 x 0.5	GY/BK	14/0.20	1.8 x 4.3	44.5	A, D	0.02
Conductor Size 0.75 mm² *								
JSF.75BKWT*	7555	2 x 0.75	BK/WH	24/0.20	2.9 x 5.9	26	B, D	0.03
JSF.75BEWT5	8602	2 x 0.75	BU/WH	24/0.20	2.9 x 5.9	26	500m	0.03
JSF.75RDBK*	3221	2 x 0.75	RD/BK	24/0.20	2.9 x 5.9	26	A, B, D	0.03
JSF.75CL1	8056	2 x 0.75	Clear	24/0.20	2.9 x 5.9	26	100m	0.03
JSF.75BK1	3899	2 x 0.75	BK	24/0.20	2.9 x 5.9	26	100m	0.03
JSF.75WT1	8051	2 x 0.75	WH	24/0.20	2.9 x 5.9	26	100m	0.03

Oxygen Free Copper

Material No.	Old Code	Cores x Area mm ²	Description	Stranding No./mm	Nom Dim mm	Max DC Resist. @ 20°C Ohms/km	Pack Size *	Approx Mass kg/m
JSF1.0CL	6288	2 x 1.0	Clear	91/0.12	2.6 x 5.7	17.2	100m	0.03
JSF2.0CL*	3865	2 x 2.0	Clear	64/0.20	3.4 x 7.0	10.9	A, D	0.05
JSF2.6CL1	6563	2 x 2.6	Clear/RD	84/0.20	4.5 x 9.0	7.4	100m	0.08

* Pack Size

Reference	Size	Code
A	100m Spool	1
B	250m Spool	250
D	500m Spool	5