



Varolex® Variable Speed Drive Cables



Wire & Cable Specification

Construction	
Standard	AS/NZS 5000.1
Voltage	0.6/1 kV
Conductor	Copper
Insulation	XLPE
Bedding	PVC
Screen	Copper tape screen
Sheath	PVC
Pack Sizes	Cut to length

Characteristics

Operating Temperature  Fixed -40°C to +90°C	Electromagnetic Compatibility  Designed for applications with EMC requirements
---	--

Application

Varolex® is a range of screened cables designed to significantly reduce interferences from electrical noise, particularly in Variable Speed Drive (VSD) applications.

Item Codes

Material No.	Old Code	Cores x Area mm ² (combined earth size)	Nom Dia mm	Gland Size (Gland Type)	Approx Mass kg/m
FTDP07AA003CXRJ	6175	3 x 2.5 + 2.5 E †	14.6	25 (VSD)	0.32
FTDP09AA003CXRJ	4005	3 x 4 + 4.5 SE	16.6	25 (VSD)	0.44
FTDP11AA003CXRJ	5206	3 x 6 + 4.5 SE	17.5	25 (A4)	0.51
FTDP13AA003CXRJ	6307	3 x 10 + 4.5 SE	18.5	25 (A4)	0.62
FTDP15AA003CXRJ	1196	3 x 16 + 7.5 SE	20.6	32 (A4)	0.86
FTDC17AA003CXRJ	7408	3 x 25 + 12 SE	22.8	32 (A4)	1.21
FTDC18AA003CXRJ	8451	3 x 35 + 18 SE	25.6	32 (A4)	1.60
FTDC19AA003CXRJ	2200	3 x 50 + 30 SE	28.8	40 (A4)	2.11
FTDC20AA003CXRJ	4466	3 x 70 + 30 SE	32.0	50S (A4)	2.77
FTDC21AA003CXRJ	9651	3 x 95 + 48 SE	38.0	50 (A4)	3.90
FTDC43AA003CXRJ	3569	3 x 120 + 48 SE	43.2	50 (A4)	4.67
FTDP24AA003CXRJ	6548	3 x 150 + 75 SE	47.3	63S (A4)	5.85
FTDP25AA003CXRJ	5985	3 x 185 + 75 SE	52.0	63 (A4)	7.11
FTDC46AA003CXRJ	4015	3 x 240 + 105 SE	58.9	75S (A4)	9.18

continued

Head Office Paraitē Road Bell Block New Plymouth New Zealand
Phone 0800 OLEX NZ (653 969) Website www.olex.co.nz

This information has been issued in good faith. The company does not accept liabilities for any misuse or unauthorised use of this document. This information can be changed without further notice. **Issue 13 July 2010 (93.3)**







Core Colours

No. Cores	Colour
4	RD, WH, BU, GNYE

Note: Conductors are circular stranded, sizes 16 mm² and above are compact circular stranded.

† Single Earth

Technical Information (Current Rating)

Conductor Size mm ²	Unenclosed		Buried Direct	Underground Ducts	Three Phase Voltage Drop mV/A.m
	Spaced from Surface	Touching			
					
Three Phase					
2.5	31	29	42	32	16.40
4	42	39	55	41	10.20
6	53	50	67	51	6.800
10	73	68	91	68	4.050
16	97	91	118	89	2.550
25	132	121	155	118	1.610
35	160	149	182	144	1.170
50	198	187	219	171	0.868
70	253	237	268	214	0.609
95	314	292	321	257	0.450

Note:

The values in this table have been obtained from AS/NZS 3008.1.2:1998 for typical New Zealand installation conditions of:-

Ambient Air Temperature	30°C
Soil Temperature	15°C
Soil Thermal Resistivity	1.2 K.m/W
Depth of Burial	0.5 m

Head Office Paraitē Road Bell Block New Plymouth New Zealand
Phone 0800 OLEX NZ (653 969) Website www.olex.co.nz

This information has been issued in good faith. The company does not accept liabilities for any misuse or unauthorised use of this document. This information can be changed without further notice. **Issue 13 July 2010 (93.3)**



INDUSTRIAL