



Datolex® Data Cable RS232



Wire & Cable Specification

Construction	
Conductor	Stranded tinned copper
Insulation	PVC
Screen	Aluminium foil overall tape with a stranded drain wire
Sheath	Grey PVC

Item Codes

Material No.	Old Code	No. of Cores	Stranding No./mm	Nom Dia mm	Max DC Resist. @ 20°C Ohms/km	Pack Size	Approx Mass kg/m
Conductor Size 0.22 mm²							
JD6CSAAA1	4240	6	7/0.20	5.5	93.3	100m	0.04
Conductor Size 0.5 mm²							
SD2CSA3	9435	2	7/0.30	5.2	37.9	300m Box	0.02
SD3CSA3	9476	3	7/0.30	5.6	37.9	300m Box	0.02

Core Colours

No. Cores	Colour
1	RD
2	BU
3	GN
4	YE

No. Cores	Colour
5	WH
6	BK
7	BN
8	VT

Olex New Zealand Limited Head Office Paraitē Road Bell Block New Plymouth New Zealand
Phone 0800 OLEX NZ (653 969) Website www.olex.co.nz

This information has been issued in good faith. The company does not accept liabilities for any misuse or unauthorised use of this document. This information can be changed without further notice. Issue 20 July 2010 (27.3)



DATA/COMMS