

Irrigation Cable Multicore



Wire & Cable Specification

Construction	
Voltage	0.6/1 kV
Conductor	Annealed copper wire
Insulation	Polypropylene
Sheath	Polyethylene

Item Codes

Material No.	Old Code	Cores x Area mm ²	Sheath	Nom Dia mm	Max DC Resist. @ 20°C Ohm/km	Approx Mass kg/m
Conductor Size 0.5 mm²						
-	1360	3 x 0.5	BU	5.1	38.4	0.03
-	9855	3 x 0.5	YE	5.1	38.4	0.03
-	3599	5 x 0.5	BU	6.0	38.4	0.04
-	4225	5 x 0.5	YE	6.0	38.4	0.04
-	5996	7 x 0.5	YE	7.0	38.4	0.05
-	5068	13 x 0.5	BU	8.9	38.4	0.12
Conductor Size 1.0 mm²						
-	7996	2 x 1.0	YE	6.4 (width)	21.2	0.03
QAEP03AA003BFAA	2741	3 x 1.0	BU	5.9	21.2	0.04
-	3965	3 x 1.0	YE	5.9	21.2	0.04
-	6186	5 x 1.0	BU	8.2	21.2	0.09
-	9513	7 x 1.0	BU	9.0	21.2	0.11
Conductor Size 1.5 mm²						
-	9660	2 x 1.5	BU	7.7 (width)	13.6	0.04
-	5526	2 x 1.5	YE	7.7 (width)	13.6	0.04
QAEP05AA003BFAA	3676	3 x 1.5	BU	8.2	13.6	0.07
-	8996	3 x 1.5	YE	8.2	13.6	0.07
QAEP05AA005BFAA	7604	5 x 1.5	BU	10.0	13.6	0.12
-	2552	5 x 1.5	YE	10.0	13.6	0.12
-	9784	7 x 1.5	BU	11.0	13.6	0.16
-	4654	7 x 1.5	YE	11.0	13.6	0.16
Conductor Size 2.5 mm²						
-	7431	2 x 2.5	BU	9.6 (width)	7.4	0.08
-	8345	2 x 2.5	YE	9.6 (width)	7.4	0.08
-	1088	5 x 2.5	BU	9.4	7.4	0.20
-	3622	7 x 2.5	BU	10.0	7.4	0.28