

## Security Cable Unscreened



### Wire & Cable Specification

Construction	
Conductor	Stranded bare copper
Insulation	PVC
Sheath	PVC

### Item Codes

Material No.	Old Code	No. Cores	Stranding No./mm	Nom Dia mm	Max DC Resist. @ 20°C Ohms/km	Pack Size *	Approx Mass kg/m
<b>Conductor Size 0.22 mm<sup>2</sup></b>							
JSC.2WT4C1	1794	4	7/0.20	3.6	86.5	100m	0.01
JSC.2WT6C1	6642	6	7/0.20	4.9	86.5	100m	0.03
<b>Conductor Size 0.44 mm<sup>2</sup></b>							
JSC.5WT4C1	6599	4	14/0.20	4.7	43.2	100m	0.03
JSC.5WT6C*	5252	6	14/0.20	5.6	43.2	A, B	0.05
JSC.5WT8C*	2613	8	14/0.20	6.5	43.2	A, D	0.06

### Core Colours

No. Cores	Core Colour
4	RD, BU, WH, BK
6	RD, BU, WH, BK, YW, GN
7	RD, BU, WH, BK, OG, YW, GN
8	RD, BU, WH, BK, VT, YW, GN, BN

### \* Pack Size

Reference	Size	Code
A	100m Spool	1
B	250m Spool	250
D	500m Spool	5